



- (51) International Patent Classification⁷:** **G01T 1/24**
- (21) International Application Number:** **PCT/GB2004/002980**
- (22) International Filing Date:** **9 July 2004 (09.07.2004)**
- (25) Filing Language:** **English**
- (26) Publication Language:** **English**
- (30) Priority Data:**
0316372.2 12 July 2003 (12.07.2003) GB
0403513.5 18 February 2004 (18.02.2004) GB
- (71) Applicant (for all designated States except US):** **RADIATION WATCH LIMITED [GB/GB];** Greenhills House, Havenstreet, Isle of Wight PO33 4DT (GB).
- (72) Inventors; and**
- (75) Inventors/Applicants (for US only):** **DOUGHTY, Peter,**


Trevor [GB/GB]; 60 Edward Road, Clevedon, Bristol BS21 7DX (GB). **ANDERSON, Michael, John** [GB/GB]; Greenhills, Havenstreet, Isle of Wight PO33 4DT (GB). **PRENDERGAST, David, Jeremy** [GB/GB]; 13 Trustwell Road, Crookes, Sheffield S10 1WH (GB). **BENSON, Ian** [GB/GB]; 170B Reading Road South, Church Crookham, Surrey GU52 6AR (GB). **MORGAN, Russell** [GB/GB]; 42 Hurstville Drive, Waterlooville, Portsmouth PO7 7NE (GB).

- (74) Agents: **POTTER, Jullan, Mark, et al.**; Mintz Levin Cohn Fems Glovsky and Popeo Intellect, ual Property LLP, The Rectory, 9 Ironmonger Lane, London EC2V 8EY (GB).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

[Continued on next page]

- (54) Title: IONISING RADIATION DETECTOR**



- (57) Abstract:** An assembly (13) for monitoring ionising radiation comprises a detector substrate (2) for generating electronic charge responsive to incident ionising radiation, the detector substrate (2) having an array of ionising radiation sense volumes (12) formed in it. A circuit substrate (14) supporting an array of read-out circuits (16) corresponding to the array of sense volumes is mechanically and electrically coupled to the detector substrate (14). Each of the read-out circuits (16) is switchable between first and second charge integration modes for receiving charge from a corresponding sense volume. A charge integration circuit (30) is configured in the first charge integration mode to integrate charge corresponding to sensing of a single ionising radiation detection event in a corresponding sense volume and in the second charge integrating mode to integrate charge corresponding to sensing a plurality of ionising radiation detection events in the corresponding sense volume. In another embodiment the read-out circuitry includes photon-counting circuitry (140).

SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NI, SN, TD, TG).

Published:

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.